



MATERIAL SAFETY DATA SHEET

For Coating, Resins and Related Materials

Approved by U.S. Department of Labor (Essentially Similar) to Form OSHA 20

Manufacturer: Tool World Inc.
Date: June 17, 2004
Emergency Phone : 800-255-3294
Emergency Contact: Chem-Tel

Address: P.O. Box 539
300 W. Norton Ave.
Eustis, FL.32726
Information: 352-357-8282
www.twidursystem.com

SECTION I PRODUCT CODE IDENTIFICATION

PRODUCT CLASS: Texture Coating

TRADE NAME: **ALL TEX**

SECTION II HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS#	OSHA PEL	ACGIH TLV
Calcium Carbonate	1317-65-3	15mg/m3	10mg/m3
Pyrophyllite	12269-78-2	15mg/m3	10mg/m3
Perlite	93763-70-3	15mg/m3	10mg/m3
Attapulgate Clay	12174-11-7	15mg/m3	10mg/m3
Talc	14807-96-6	20mppcf	2 respirable dust
Starch	9005-25-8	15mg/m3	15mg/m3
Defoamer	64741-89-5	5mg/m3	5mg/m3
Ziram	137-30-4	Not established	Not established
Magnesium	1309-48-4	15mg/m3	15mg/m3

SECTION III PHYSICAL DATA

BOILING RANGE: N/A

VAPOR DENSITY: N/A

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: < 5%

WEIGHT PER GALLON: N/A

MATERIAL IS A DRY POWDER

SECTION IV FIRE AND EXPLOSION DATA

DOT CATEGORY: Non Regulated

FLASH POINT: N/A Dry powder, non combustible

SPECIAL FIRE FIGHTING PROCEDURES: Will not burn under normal circumstances

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 10mg/m3(total dust) 5mg/m3 (respirable dust) Nuisance Dust

EFFECTS OF OVEREXPOSURE: *Inhalation* - Do not breath dust. Prolonged inhalation of excessive dust may cause lung injury or other respiratory ailments. *Skin Contact* - Possible irritant (slightly alkaline). *Eye Contact* - Irritation. Flush eye with water for 5 minutes is a good safety practice.

EMERGENCY AND FIRST AID PROCEDURES: *Inhalation* - Remove to fresh air. Restore breathing. Consult Physician.

Skin contact - Wash affected areas with soap and water. Remove contaminated clothing.

Eye Contact - Flush immediately with large amounts of water for at least 15 minutes. Consult Physician.

SECTION VI REACTIVITY DATA

STABILITY: Unstable_____ Stable__X__

HAZARDOUS DECOMPOSITION: Thermal decomposition or burning may produce Carbon Monoxide.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VII SPILL OR LEAK PROCEDURES

SPILLED OR RELEASED MATERIAL : Sweep, shovel or vacuum material into waste container for disposal.

WASTE DISPOSAL METHOD : Collect and dispose of in accordance with all local, state, and federal laws.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATOR PROTECTION : Use NIOSH/MSHA approved respirator for dust and mists.

GLOVES : Neoprene gloves for skin protection.

EYE PROTECTION : Use protective goggles or face shield.

OTHER PROTECTIVE EQUIPMENT : Protective cream where skin contact is likely.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS FOR HANDLING AND STORAGE : Keep dry . Do not get in eyes.

OTHER PRECAUTIONS : Prevent prolonged breathing of dust. Avoid creating dust.

SECTION X MISCELLANEOUS DATA

The data set forth on this sheet is based on information provided by the suppliers of the raw materials and chemicals used in the production and manufacture of the aforementioned products. TOOL WORLD INC. makes no warranty with respect to the accuracy of the information provided by the suppliers, and disclaims all liability or reliance thereof.

PRODUCT : ***ALL TEX***

DATE : June 17, 2004

PREPARED BY : Alan Semento