



# DS 3000

## 100% Acrylic Texture Coating

**Product Category:**

Acrylic Textures

**Product Line:**

Dursystem® Acrylic Textures

**Product Name:**

DS 3000

**Manufacturer:**

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ (800) 331-8273

☎ (352) 357-8282

Fax (352) 357-1417

[www.twidursystem.com](http://www.twidursystem.com)



5 Gal Pail

55 Gal Drum  
(Items not to scale)

275 Gal Tote

### Product Description

*Dursystem® DS 3000* 100% Acrylic Texture Coating is a durable, high solids, non-aggregated acrylic texture coating that creates a variety of textures such as orange peel, splatter, knockdown, or hand applied textures. *DS 3000* is designed to hide minor surface imperfections and can be applied over gypsum wallboard, plaster, wood, and cured concrete surfaces.

### Advantages

*DS 3000* is a decorative, integral colored, mildew resistant acrylic texture coating that can be applied as both a durable base coat, and as a decorative texture, over new or renovated gypsum wallboard. When applied as a full coverage base coat and texture top coat, *DS 3000* gives higher production rates and better touch-up capabilities than most texture products. *DS 3000* is formulated with a 100% acrylic resin and is non-abrasive. Due to its hardness, *DS 3000* is ideal for high traffic areas and has good holdout when sheen paints are specified as a final coat.

### Surface Preparation

Surfaces shall be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss.

1. New gypsum wallboard surfaces and accessories should be primed with *DS 3000* base coat or *DS 750* Acrylic Primer Sealer prior to *DS 3000* texture application.
2. Concrete, plaster, and masonry surfaces must be smooth and cured thoroughly, then sealed with *DS 750* 100% Acrylic Primer/Sealer prior to *DS 3000* application. Prime rust areas with rust-inhibiting primer. Allow new concrete to cure 30 days.
3. Painted surfaces should be dulled and primed with *DS 750* 100% Acrylic Primer/Sealer or an appropriate bonding primer prior to *DS 3000* application.

**Product Data**

**MATERIAL:** 100% Acrylic

**COLOR:** White. Can be tinted at store level with most color systems to a variety of pastel or mid-tone colors. (Use up to 8 oz. of universal colorant per five gallons.)

**PRODUCT SENSITIVITY:** Do not apply when temperatures are below 50°F or above 95° F.

**MIXING:** Mix material thoroughly. If thinning is necessary, do not exceed one pint of clean water per five gallons.

**DO NOT OVER-THIN PRODUCT.**

**APPLICATION:** Base Coat: Apply with airless sprayer (min. 1.25 gpm) using .023 - .025 tip, min. 3/8" airless hose, and remove all filters.

Texture Coat: Brush, roller, hopper gun, portable texture machine, airless sprayer (min. 1.25 gpm) with texture atomizer assisted by air compressor (min. 9 cfm).

**COVERAGE:** Varies on surface and equipment.

Base Coat: 100-125 ft<sup>2</sup> per gallon @ 16 mils wet.

Texture: 110 ft<sup>2</sup> (Varies on texture desired)

**DECORATION:** Can be painted or left unpainted.

**STORAGE:** Do not store material in direct sunlight, or in temperatures below 32°F.

Good storage conditions will allow up to 12 months shelf life.

**PROTECT FROM FREEZING.**

**PACKAGING:** 5 gal. pail, 55 gal. drum, and 275 gal. tote

**WARRANTY:** If *DS 3000* fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

**SAFETY PRECAUTIONS:** When dry sanding or spraying, wear eye protection and respirator that are NIOSH approved.

**Submittal Approval**

Job Name: \_\_\_\_\_

Job Location: \_\_\_\_\_

Contractor: \_\_\_\_\_

Approved by: \_\_\_\_\_

Title: \_\_\_\_\_

Date: \_\_\_\_\_

TWI  
300 W. Norton Ave.  
Eustis, FL 32726  
800-331-8273