



JOINT BUTTER®

Ready-Mixed Joint Compound

Product Category:

Joint Treatments

Product Name:

JOINT BUTTER®

Product Grade:


All Purpose


Manufacturer:

TWI

300 W. Norton Ave.

Eustis, FL 32726

 (800) 331-8273

 (352) 357-8282

Fax (352) 357-1417

www.twidursystem.com



50 lb. Carton



62 lb. Pail

Product Description

JOINT BUTTER® is a premixed, ready-to-use, vinyl based joint compound ideal for all phases of gypsum wallboard finishing. JOINT BUTTER® may also be used to skim coat, texture, and repair plaster.

Advantages

JOINT BUTTER® is formulated to provide superior working qualities such as; low shrinkage, excellent adhesion, good crack resistance, excellent sanding qualities, and easy workability.

Surface Preparation

Surfaces should be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss. Do not apply to shower areas directly exposed to water.

1. Assure that all fasteners and joints are thoroughly dry prior to decorating.
2. New gypsum wallboard surfaces that are to be painted or textured should be primed with TWI's *DURLAST* drywall primer or *SPRAY PLAST* Level 5 Primer/Surfacer.
3. Concrete, plaster, and masonry surfaces must be sealed with *DS 750* 100% Acrylic Primer/Sealer. Allow new concrete to cure 30 days.

Product Data

MATERIAL: Vinyl type

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50° F or above 95° F.

MIXING: Mix thoroughly. Do not exceed one pint of clean water per 3.5 gal. (50 lb) carton for finishing.

DO NOT OVER-THIN PRODUCT.

APPLICATION: Hand or mechanical

COVERAGE: Approximately 125 lb. to 145 lb./1,000 ft.² (depending on surface and application)

COMPLIANCE WITH STANDARDS: Meets ASTM C475

STORAGE: Do not store material in direct sunlight, or in temperatures below 32° F.

Good, dry storage conditions will allow up to 9 months shelf life.

PROTECT FROM FREEZING.

PACKAGING: 3.5 gal. (50 lb) carton and 4.5 gal. (62 lb) pail

WARRANTY: If TWI's *JOINT BUTTER*[®] fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding or spraying, wear eye protection and respirator that are NIOSH approved.

Submittal Approval

Job Name: _____

Job Location: _____

Contractor: _____

Approved by: _____

Title: _____

Date: _____

TWI
300 W. Norton Ave.
Eustis, FL 32726
800-331-8273