



## MATERIAL SAFETY DATA SHEET

*For Coating, Resins and Related Materials*

Approved by U.S. Department of Labor (Essentially Similar) to Form OSHA 20

**Manufacturer:** Tool World Inc.  
**Date:** June 17, 2004  
**Emergency Phone :** 800-255-3294  
**Emergency Contact:** Chem-Tel

**Address:** P.O. Box 539  
300 W. Norton Ave.  
Eustis, FL.32726  
**Information:** 352-357-8282  
[www.twidursystem.com](http://www.twidursystem.com)

### SECTION I

### PRODUCT CODE IDENTIFICATION

PRODUCT CLASS: Texture Coating

TRADE NAME: **POLY SUPREME**  
Fine or Medium

### SECTION II

### HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS#	OSHA PEL	ACGIH TLV
Calcium Carbonate	1317-65-3	15mg/m3	10mg/m3
Pyrophyllite	12269-78-2	15mg/m3	10mg/m3
Attapulgate Clay	12174-11-7	15mg/m3	10mg/m3
Talc	14807-96-6	20mppcf	2 respirable dust
Starch	9005-25-8	15mg/m3	15mg/m3
Polystyrene	9003-53-6	Not established	Not established
Defoamer	64741-89-5	5mg/m3	5mg/m3
Ziram	137-30-4	Not established	Not established
Magnesium	1309-48-4	15mg/m3	15mg/m3

### SECTION III

### PHYSICAL DATA

BOILING RANGE: N/A

VAPOR DENSITY: N/A

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: < 5%

WEIGHT PER GALLON: N/A

MATERIAL IS A DRY POWDER

### SECTION IV

### FIRE AND EXPLOSION DATA

DOT CATEGORY: Non Regulated

FLASH POINT: N/A Dry powder, non combustible

SPECIAL FIRE FIGHTING PROCEDURES: Will not burn under normal circumstances

### SECTION V

### HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 10mg/m3(total dust) 5mg/m3 (respirable dust) Nuisance Dust

EFFECTS OF OVEREXPOSURE: *Inhalation* - Do not breath dust. Prolonged inhalation of excessive dust may cause lung injury or other respiratory ailments. *Skin Contact* - Possible irritant (slightly alkaline). *Eye Contact* - Irritation. Flush eye with water for 5 minutes is a good safety practice.

EMERGENCY AND FIRST AID PROCEDURES: *Inhalation* - Remove to fresh air. Restore breathing. Consult Physician.

*Skin contact* - Wash affected areas with soap and water. Remove contaminated clothing.

*Eye Contact* - Flush immediately with large amounts of water for at least 15 minutes. Consult Physician.

**SECTION VI REACTIVITY DATA**

STABILITY: Unstable\_\_\_\_\_ Stable\_\_X\_\_

HAZARDOUS DECOMPOSITION: Thermal decomposition or burning may produce Carbon Monoxide.

HAZARDOUS POLYMERIZATION: Will not occur

**SECTION VII SPILL OR LEAK PROCEDURES**

SPILLED OR RELEASED MATERIAL : Sweep, shovel or vacuum material into waste container for disposal.

WASTE DISPOSAL METHOD : Collect and dispose of in accordance with all local, state, and federal laws.

**SECTION VIII SPECIAL PROTECTION INFORMATION**

RESPIRATOR PROTECTION : Use NIOSH/MSHA approved respirator for dust and mists.

GLOVES : Neoprene gloves for skin protection.

EYE PROTECTION : Use protective goggles or face shield.

OTHER PROTECTIVE EQUIPMENT : Protective cream where skin contact is likely.

**SECTION IX SPECIAL PRECAUTIONS**

PRECAUTIONS FOR HANDLING AND STORAGE : Keep dry . Do not get in eyes.

OTHER PRECAUTIONS : Prevent prolonged breathing of dust. Avoid creating dust.

**SECTION X TRANSPORT INFORMATION**

U.S. DOT INFORMATION: Not a hazardous material per DOT shipping requirements. Not classified or regulated.

**SECTION XI MISCELLANEOUS DATA**

The data set forth on this sheet is based on information provided by the suppliers of the raw materials and chemicals used in the production and manufacture of the aforementioned products. TOOL WORLD INC. makes no warranty with respect to the accuracy of the information provided by the suppliers, and disclaims all liability or reliance thereof.

PRODUCT : **POLY SUPREME** Fine or Medium

DATE : June 17, 2004

PREPARED BY : Alan Semento