



MATERIAL SAFETY DATA SHEET

For Coating, Resins and Related Materials

Approved by U. S. Department of Labor (Essentially Similar) to Form OSHA 20

Manufacturer : Tool World Inc.
Date : June 17, 2004
Emergency Phone : 800-255-3924
Emergency Contact : Chem-Tel

Address : P.O. Box 539
300 W. Norton Ave.
Eustis, FL. 32726
Information: 352-357-8282
www.twidursystem.com

SECTION I PRODUCT CODE IDENTIFICATION

PRODUCT CLASS : Drywall Textures

TRADE NAME : **READY-MIX TEXTURE**

SECTION II HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS #	OSHA PEL	ACGIH TLV
Calcium Carbonate	1317-65-3	15mg/m3	10mg/m3
Attapulgite Clay	12174-11-7	15mg/m3	10mg/m3
Perlite	93763-70-3	15mg/m3	15mg/m3
Mica	12001-26-2	20 mppcf	3 respirable dust
Vinyl Acetate Monomer	108-05-4	10 ppm	10 ppm
Magnesium	1309-48-4	15mg/m3	10mg/m3
Ethylene Glycol	107-21-1	50 ppm	50 ppm

SECTION III PHYSICAL DATA

BOILING RANGE: Approx. 200 F.

VAPOR DENSITY: Lighter than air

EVAPORATION RATE : Slower than Ether

% VOLATILE : 52

WEIGHT PER GALLON : 13.6 lbs.

V.O.C. 0.30 lbs/gal 36.2 gm/l

SECTION IV FIRE AND EXPLOSION DATA

DOT CATEGORY: Non-Regulated

FLASH POINT: >200 F.

EXTINGUISHING MEDIA: Water based coating. Will not burn under normal circumstances.

SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool containers to prevent pressure build up.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Containers may explode if exposed to extreme heat.

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 10mg/m3 (total dust) 5mg/m3 (respirable dust).

EFFECTS OF OVEREXPOSURE: *Inhalation* - May cause headache and nausea. *Skin contact* - Possible irritant (material is slightly alkaline) *Eye contact* - Primary irritant.

EMERGENCY AND FIRST AID PROCEDURES: *Inhalation* - Remove to fresh air. Consult physician.

Skin Contact - Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician.

Eye Contact - Flush immediately with large amounts of water for at least 15 minutes. Consult a physician.

SECTION VI REACTIVITY DATA

STABILITY: Unstable ____ Stable X

HAZARDOUS DECOMPOSITION: Thermal decomposition or burning may produce Carbon Monoxide.

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Avoid extreme temperatures - below 40 F - above 190 F.

SECTION VII**SPILL OR LEAK PROCEDURES**

SPILLED OR RELEASED MATERIAL: Sweep, shovel or vacuum material into waste container for disposal.
WASTE DISPOSAL: Collect and dispose of in accordance with all local, state, and federal laws.

SECTION VIII**SPECIAL PROTECTION INFORMATION**

RESPIRATOR PROTECTION: Use NIOSH/MSHA approved respirator for dust and mists when necessary.
GLOVES: Neoprene gloves for skin protection.
EYE PROTECTION: Use protective goggles or face shield.
OTHER PROTECTIVE EQUIPMENT: Protective cream where skin contact is likely.

SECTION IX**SPECIAL PRECAUTIONS**

PRECAUTIONS FOR HANDLING AND STORAGE: Keep dry. Do not get in eyes.
OTHER PRECAUTIONS: Prevent prolonged breathing of dust. Avoid creating dust.

SECTION X**TRANSPORT INFORMATION**

U.S. DOT INFORMATION: Not a hazardous material per DOT shipping requirements. Not classified or regulated.

SECTION XI**MISCELLANEOUS DATA**

The data set forth on this sheet is based on information provided by the suppliers of the raw materials and chemicals used in the production and manufacture of the aforementioned products. TOOL WORLD INC. makes no warranty with respect to the accuracy of the information provided by the suppliers, and disclaims all liability or reliance thereof.

PRODUCT: ***READY-MIX TEXTURE***

DATE: June 17, 2004

PREPARED BY: Alan Semento