



NUTEX™

All Purpose Surfacers/Texture

Product Category:

Drywall Textures

Product Name:

NUTEX™

Manufacturer:

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ (800) 331-8273

☎ (352) 357-8282

Fax (352) 357-1417

www.twidursystem.com



5 Gal Pail



55 Gal Drum



275 Gal Tote

(Items not to scale)

Product Description

NUTEX™ is a non-aggregated vinyl based, economical texture formulated to create a variety of textures such as orange peel, knockdown, splatter, skip trowel, stipple, glazing, or hand applied texture. NUTEX™ is designed to hide minor surface defects and can be applied over gypsum wallboard, plaster, or concrete surfaces.

Advantages

NUTEX™ is specifically formulated to give more consistency, superior workability, and a higher profile texture than most joint compounds and bag textures. NUTEX™ dries to a harder finish that provides a more even absorption rate and better coverage for the finish paint. Because of its superior hardness, NUTEX™ is less likely to rewet, when painted, than joint compound and bag textures. NUTEX™ dries white and can be painted or left unpainted on noncontact ceilings. NUTEX™ eliminates the need for expensive mixing spray equipment without sacrificing productivity. Because of its smooth consistency, it is ideal for airless spray equipment, using the texture atomizer.

Surface Preparation

Surfaces should be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss.

1. New gypsum wallboard surfaces and accessories should be primed with *DURLAST* drywall primer or NUTEX™ base coat prior to NUTEX™ texture application.
2. Concrete, plaster, and masonry surfaces must be smooth and cured thoroughly, then sealed with *DS 750 100% Acrylic Primer/Sealer* prior to NUTEX™ application. Prime rust areas with a rust-inhibiting primer. Allow new concrete to cure for 30 days.
3. Painted surfaces should be dulled and primed with *DS 750 100% Acrylic Primer/Sealer* or an appropriate bonding primer prior to NUTEX™ application.

Product Data

MATERIAL: Vinyl type

COLOR: White

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50°F or above 95°F.

MIXING: Mix thoroughly. Add clean water in one pint increments to achieve desired viscosity.

DO NOT OVER-THIN PRODUCT.

APPLICATION: Brush, roller, hopper gun, portable texture machine, piston or stator type machine, airless sprayer (min. 1.25 gpm) using a .023-.027 tip for smooth application or with texture atomizer and air compressor (min. 9 cfm) to achieve texture desired.

COVERAGE: Approximately 75-150 ft² per gallon. (Varies on surface, equipment, and texture desired)

DECORATION: Not intended as final coat, should be painted when dry. Can be left unpainted on noncontact ceilings.

STORAGE: Do not store material in direct sunlight, or in temperatures below 32°F.

Good, dry storage conditions will allow up to 9 months shelf life.

PROTECT FROM FREEZING.

PACKAGING: 3.5 gallon carton, 5 gallon pail, 55 gallon drum, and 275 gallon tote.

WARRANTY: If *TWINUTEX*™ fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding or spraying, wear eye protection and a respirator that are NIOSH approved.

Submittal Approval

Job Name: _____

Job Location: _____

Contractor: _____

Approved by: _____

Title: _____

Date: _____

TWI
300 W. Norton Ave.
Eustis, FL 32726
800-331-8273