



READY-MIX TEXTURE

Non-Aggregated Wall and Ceiling Texture

Product Category:

Drywall Textures

Product Name:

READY-MIX TEXTURE

Manufacturer:

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ (800) 331-8273

☎ (352) 357-8282

Fax (352) 357-1417

www.twidursystem.com



3.5 Gal Carton



5 Gal Pail



275 Gal Tote

(Items not to scale)

Product Description

READY-MIX TEXTURE is an non-aggregated, premixed vinyl base, economical texture formulated to create a variety of textures such as orange peel, knockdown, splatter, skip trowel, stipple, glazing, or hand applied textures. READY-MIX TEXTURE is designed to hide minor surface defects and can be applied over gypsum wallboard, plaster, or concrete surfaces. READY-MIX TEXTURE is ideal for rolling or spraying with an airless sprayer as a skim coat over gypsum surfaces that are damaged or have had vinyl wallcoverings removed.

Advantages

READY-MIX TEXTURE is specifically formulated to give more consistency, superior workability, and gives a higher profile texture than most joint compounds and bag textures. READY-MIX TEXTURE eliminates the need for expensive mixing spray equipment without sacrificing productivity. Because of its smooth consistency, it is ideal for airless spray equipment, using the texture atomizer.

Surface Preparation

Surfaces shall be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss.

1. New gypsum wallboard surfaces and accessories should be primed with *DURLAST* drywall primer prior to *READY-MIX TEXTURE* application.
2. Concrete, plaster, and masonry surfaces must be smooth and cured thoroughly, then sealed with *DS 750* 100% Acrylic Primer/Sealer prior to *READY-MIX TEXTURE* application. Prime rust areas with rust-inhibiting primer. Allow new concrete to cure 30 days.
3. Painted surfaces should be dulled and primed with *DS 750* 100% Acrylic Primer/Sealer or an appropriate bonding primer prior to *READY-MIX TEXTURE* application.

Product Data

MATERIAL: Vinyl type

COLOR: White

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50°F or above 95°F.

MIXING: Mix thoroughly. Add clean water in one pint increments to achieve desired viscosity.

DO NOT OVER-THIN PRODUCT.

APPLICATION: Brush, roller, hopper gun, portable texture machine, piston or stator type machine, airless sprayer (min. 1.25 gpm) with texture atomizer and air compressor (min. 9 cfm).

COVERAGE: Approximately 75-150 ft² per gallon. (Varies on surface, equipment, and texture desired)

DECORATION: Not intended as final coat. Should be painted when dry.

STORAGE: Do not store material in direct sunlight, or in temperatures below 32°F.

Good, dry storage conditions will allow up to 9 months shelf life.

PROTECT FROM FREEZING.

PACKAGING: 3.5 gallon carton, 5 gallon pail, and 275 gallon tote.

WARRANTY: If TWI's *READY-MIX TEXTURE* fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding or spraying, wear eye protection and a respirator that are NIOSH approved.

Submittal Approval

Job Name: _____

Job Location: _____

Contractor: _____

Approved by: _____

Title: _____

Date: _____

TWI
300 W. Norton Ave.
Eustis, FL 32726
800-331-8273