



ALL TEX

Non-Aggregated Wall and Ceiling Texture

Product Category:

Drywall Textures

Product Line:

Acusti-Tex

Product Name:

ALL TEX

Manufacturer:

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ (800) 331-8273

☎ (352) 357-8282

Fax (352) 357-1417

www.twidursystem.com



All Purpose



Multi-Purpose

Product Description

ALL TEX is an non-aggregated, dry powder, and economical texture formulated to create a variety of textures such as orange peel, knockdown, splatter, skip trowel, stipple, or hand applied textures. ALL TEX is designed to hide minor surface defects and can be applied over gypsum wallboard, plaster, or concrete surfaces.

Advantages

ALL TEX is specifically formulated to give a higher profile texture, mixes easily, and has minimal fallout. ALL TEX is available in both All Purpose and Multi-Purpose grades.

1. All Purpose is designed for larger crews due to its faster drying time.
2. Multi-Purpose is designed for smaller crews due to its longer open time.

Surface Preparation

Surfaces shall be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss.

1. New gypsum wallboard surfaces and accessories should be primed with DURLAST drywall primer prior to ALL TEX application.
2. Concrete, plaster, and masonry surfaces must be smooth and cured thoroughly, then sealed with DS 750 100% Acrylic Primer/Sealer prior to ALL TEX application. Prime rust areas with rust-inhibiting primer. Allow new concrete to cure 30 days.
3. Painted surfaces should be dulled and primed with DS 750 100% Acrylic Primer/ Sealer or an appropriate bonding primer prior to ALL TEX application.

Product Data

MATERIAL: Dry powder

COLOR: White

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50°F or above 95°F.

MIXING: Add enough clean water to produce thick texture. Let stand for approximately 15 minutes, before adding additional clean water to adjust viscosity.

DO NOT OVER-THIN PRODUCT.

APPLICATION: Hopper gun, portable texture machine, airless sprayer (min. 1.25 gpm) with texture atomizer and air compressor (min. 9 cfm), piston or stator type machine.

COVERAGE: Approximately 500-1000 ft² /50 lb. bag. (depending on surface and equipment)

DECORATION: Not intended as final coat. Should be painted when dry.

COMPLIANCE WITH STANDARDS: Meets ASTM E84

STORAGE: Good, dry storage conditions will allow up to 12 months shelf life.

PACKAGING: 50 lb. plastic-lined bags.

WARRANTY: If TWI *ALL TEX* fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding, mixing or spraying, wear proper eye protection and respirator that are NIOSH approved .

Submittal Approval

Job Name: _____

Job Location: _____

Contractor: _____

Approved by: _____

Title: _____

Date: _____

TWI
300 W. Norton Ave.
Eustis, FL 32726
800-331-8273