



POLY SUPREME

Aggregated Ceiling Texture

Product Category:

Drywall Textures

Product Line:

Acusti-Tex™

Product Name:

POLY SUPREME

Manufacturer:

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ (800) 331-8273

☎ (352) 357-8282

Fax (352) 357-1417

www.twidursystem.com



Medium



Fine

Product Description

POLY SUPREME ceiling spray texture is a polystyrene aggregate, decorative texture which creates a uniform textured ceiling. *POLY SUPREME* is available in fine or medium aggregate and is designed to hide minor surface defects. *POLY SUPREME* can be applied over gypsum wallboard, plaster, or concrete ceilings.

Advantages

POLY SUPREME is specifically formulated to have excellent wet and dry hide properties, mix easily, and have minimal fallout. *POLY SUPREME* dries white and can be painted or left unpainted on noncontact ceilings.

Surface Preparation

Surfaces shall be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss.

1. New gypsum wallboard surfaces and accessories should be primed with *DURLAST* drywall primer prior to *POLY SUPREME* application.
2. Concrete, plaster, and masonry surfaces must be smooth and cured thoroughly, then sealed with *DS 750 100% Acrylic Primer/Sealer* prior to *POLY SUPREME* application. Prime rust areas with rust-inhibiting primer. Allow new concrete to cure 30 days.
3. Painted surfaces should be dulled and primed with *DS 750 100% Acrylic Primer/Sealer* or an appropriate bonding primer prior to *POLY SUPREME* application.

Product Data

MATERIAL: Dry powder

COLOR: White

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50°F or above 95°F.

MIXING: Add enough clean water to produce thick texture. Let stand for approximately 15 minutes, before adding additional clean water to adjust viscosity.

DO NOT OVER-THIN PRODUCT.

APPLICATION: Hopper gun, portable texture machine, piston or stator type texture machine.

COVERAGE: Approximately 250-350 ft² /40 lb. bag. (depending on surface and equipment)

COMPLIANCE WITH STANDARDS: Meets ASTM E84

STORAGE: Good, dry storage conditions will allow up to 12 months shelf life.

PACKAGING: 40 lb. plastic-lined bags.

WARRANTY: If TWI *POLY SUPREME* fails to perform as specified when applied according to specifications, TWI's liability shall be limited to the refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding, mixing or spraying, wear eye protection and respirator that are NIOSH approved.

Submittal Approval

Job Name: _____

Job Location: _____

Contractor: _____

Approved by: _____

Title: _____

Date: _____

TWI
300 W. Norton Ave.
Eustis, FL 32726
800-331-8273