



®

# SPRAY PLAST

## Builders Select

### Level 5 Primer/Surfacer

**Product Category:**

Level 5 Primers

**Product Name:**

SPRAY PLAST®

**Product Grade:**

Builders Select

**Manufacturer:**

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ (800) 331-8273

☎ (352) 357-8282

☎ Fax (352) 357-1417

[www.twidursystem.com](http://www.twidursystem.com)

5 Gal Pail

55 Gal Drum

275 Gal Tote

(Items not to scale)

#### Product Description

SPRAY PLAST® Builders Select is an interior, high solids, level 5 drywall primer/surfacer, that when applied over a level 4 gypsum wallboard finish achieves a level 5 finish. SPRAY PLAST® Builders Select in accordance with GA-214/ASTM C-840 gypsum board finish specifications, achieves a level 5 finish, which is the highest quality drywall finish.

SPRAY PLAST® Builders Select is specifically formulated to equalize the porosity difference between the wallboard surface and joint compound, which will allow for final coat(s) of paint to dry at a uniform rate.

#### Advantages

SPRAY PLAST® Builders Select is an economical, easy to sand, level 5 drywall primer/surfacer that is designed to eliminate joint flashing and hide minor surface imperfections, while replacing primer and/or first coat of paint. It also eliminates a costly two-step process of a skim coat over the entire gypsum wallboard surface and primer coat, in one spray application. SPRAY PLAST® Builders Select is ideal for new drywall on residential and commercial projects.

#### Surface Preparation

Surfaces shall be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss.

1. New gypsum wallboard surfaces and accessories should be treated with *JOINT BUTTER* as per instructions, must be smooth and dry thoroughly prior to SPRAY PLAST® Builders Select application.
2. Concrete, plaster, and masonry surfaces must be smooth and cured thoroughly, then sealed with *DS 750 100% Acrylic Primer/Sealer* prior to SPRAY PLAST® Builders Select application. Prime rust areas with a rust-inhibiting primer. Allow new concrete to cure for 30 days.

**Product Data**

MATERIAL: Vinyl Acrylic

COLOR: White. May be tinted up to 1 oz. per gallon of universal colorant.

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50°F or above 95°F.

MIXING: Stir material thoroughly.

**DO NOT OVER-THIN PRODUCT.**

APPLICATION: Airless spray machine. (1.25 gpm) using .023-.027 tip and 30 mesh filter.

COVERAGE: Approximately 100-150 ft² per gallon, depending on surface and equipment.

DECORATION: Dries to touch in 30-90 minutes under 75°F/50% relative humidity conditions.

**NOT INTENDED AS FINAL COAT. SHOULD BE OVERPAINTED WHEN DRY.**

STORAGE: Do not store material in direct sunlight, or in temperatures below 32°F.

Good storage conditions will allow up to 12 months shelf life.

**PROTECT FROM FREEZING.**

PACKAGING: 5 gallon pail, 55 gallon drum, and 275 gallon tote.

WARRANTY: If *SPRAY PLAST® Builders Select* fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding wear proper eye protection and a NIOSH approved respirator.

**Submittal Approval**

Job Name: \_\_\_\_\_

Job Location: \_\_\_\_\_

Contractor: \_\_\_\_\_

Approved by: \_\_\_\_\_

Title: \_\_\_\_\_

Date: \_\_\_\_\_