



SPRAY-PLAST[®]

Level 5 Drywall Surfacer

Product Category:

Dursystem[®] Products

Product Name:

Spray-Plast[®] Level 5 Drywall Surfacer

Manufacturer:

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ (800) 331-8273

☎ (352) 357-8282

Fax (352) 357-1417

www.twidursystem.com



Product Description

Spray-Plast[®] Level 5 Drywall Surfacer is a high build coating which - when applied over a level 4 drywall finish - creates a durable, primed, level 5 wall surface.

Advantages

Spray-Plast[®] Level 5 Drywall Surfacer creates, in one coat, a build and appearance superior to several coats of a conventional primer while eliminating time consuming sanding steps.

Spray-Plast[®] Level 5 Drywall Surfacer is also used as an economical block filler.

Surface Preparation

Surfaces shall be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss prior to *Spray-Plast*[®] Level 5 Drywall Surfacer application.

1. Drywall: Treat all joints and nail heads with *JOINT BUTTER* as per instructions. Assure that all surfaces, including joints and nail heads are dry prior to *Spray-Plast*[®] Level 5 Drywall Surfacer application.
2. Concrete and masonry: Caulk and buff surface. Allow new concrete to cure for 28 days. Prime rust areas with a rust-inhibiting primer.

Product Data

MATERIAL: Vinyl Acrylic

COLOR: White or Off White. Can be tinted in the field.

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50° F or above 95° F.

MIXING: Mix material thoroughly. If thinning is necessary, do not exceed one pint of clean water per gallon.

DO NOT OVER-THIN PRODUCT.

APPLICATION: Brush, roller, or airless spray machine. (.75 gpm)

COVERAGE: Approximately 150-300 ft per gallon, depending on surface and equipment.

DECORATION: Dries to touch in 30 minutes under 75°F/50% relative humidity conditions.

NOT INTENDED AS FINAL COAT. SHOULD BE OVERPAINTED WHEN DRY.

STORAGE: Good storage conditions will allow up to 12 months shelf life.

KEEP FROM FREEZING.

PACKAGING: 5 gallon pail, 55 gallon drum, and 275 gallon tote.

WARRANTY: If *Spray-Plast*® Level 5 Drywall Surfacers fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding wear proper eye protection and a NIOSH approved respirator.

Submittal Approval

Job Name: _____

Job Location: _____

Contractor: _____

Approved by: _____

Title: _____

Date: _____

TWI
300 W. Norton Ave.
Eustis, FL 32726
800-331-8273